

comet

x-ray

SMART EVO 300P



comet SMART EVO 300P

PIPELINE CRAWLERS • BETATRON PORTABLE X-RAY • DIGITAL RADIOGRAPHY

The SMART EVO 300P features a combination of 300 kV and 750 W constant potential X-ray power for high penetration - making it well suited for all heavy duty inspection jobs where ultimate performance is required.

BUILT TO LAST

IT'S ROBUST AND RELIABLE

The SMART EVO systems are comprised of the best components and assembled with the utmost care - making them reliable, long lasting and a sound investment. They are fitted with a high quality metal ceramic X-ray tube and the robust composite casing now protects all vital parts even better. The systems meet the IP65 standard, making them fully operational in dusty and wet conditions.

SMARTER WORKFLOW

IT'S LIGHT-WEIGHT AND EASY TO HANDLE

The ergonomic design and the compact size make the SMART EVO 200P easy to handle and re-position. A broad temperature range from -20°C to +50°C makes the EVO systems reliable and ensures smooth operation even in extreme environments. The intuitive interface allows for a smarter workflow. The re-engineered three-part lead belt is easy to mount and has as standard a 38° x 60° slit option allowing for directional use if required.

HIGH PERFORMANCE

DUE TO ITS TECHNICAL CAPABILITIES

Built to meet the highest international safety standards, each unit is individually tested and measured for safety and accuracy. The panoramic 38° x 360° X-ray beam makes the SMART EVO a perfect choice for weld seam inspection of cylindrical vessels and pipes. The SMART EVO 200P features a combination of 30 - 200 kV and 750 W constant potential X-ray power for high penetration - making it well suited for a broad range of inspection jobs where reliability and performance is required.

comet

PRODUCT RANGE



SMART EVO 200P / 300P



SMART EVO DIRECTIONAL



XPO EVO DIRECTIONAL



SMART EVO WATER-COOLED



Y.XMB



PROUDLY SUPPLYING THE NDT INDUSTRY FOR OVER 35 YEARS

JME

ADVANCED INSPECTION SYSTEMS

CALL OUR SALES TEAM FOR MORE INFORMATION

+44 (0)1502 500969

JME LTD. ELECTRON HOUSE, OLD NELSON STREET
LOWESTOFT, SUFFOLK NR32 1EQ UNITED KINGDOM


FIND JME ONLINE...

www.jme.co.uk

f /JMElimited | @JME_NDT | in jme-advanced-inspection-systems



Fe EXPOSURE DIAGRAM
700 mm FFD / D7-type + Pb / D = 2,0



EXPOSURE CALCULATOR

The advanced built-in exposure calculator in the CONTROL EVO ensures fast exposure calculations, as well as uniform results and optimised exposure times. It accommodates the use of a wide range of films, materials and settings.

POWER SUPPLY

The AC-mains voltage range spans from 85 to 264 VAC and from 45 to 65 Hz, supporting global operation. The improved power factor correction module ensures stable operation, where AC-mains are unstable.

OPTIONS

The right set of accessories is important to make your workflow even smarter. A tube stand and other accessories are available, making the X-ray systems versatile, flexible and suited for most applications.

CERTIFICATES

CE (Low voltage EN 61010-1, EMC 2004/108/EC, Machinery EN 60204-1). DIN 54113.

EXCLUSIVE UNITED KINGDOM DISTRIBUTOR

From the early days of Andrex and SMART systems, Comet's product range has been built on an excellent reputation for innovation, reliability and performance. Power options range from 160 to 300kV; this combined with light weight construction and an intuitive user interface means there is a Comet X-ray generator to suit every application.

JME have been manufacturing high quality NDT products since 1986 and are proud to be the UK exclusive distributor for Comet products. JME have Comet trained technical staff on hand to ensure support is always available. JME offers the complete Comet range of X-ray products and our knowledgeable sales team will handle all of your enquiries efficiently.

TECHNICAL SPECIFICATIONS

Weight	36 kg
Height	804 mm
Focal Spot Size EN 12543	0.5 x 5.5 mm
High Voltage Adjustment	50 - 200 kV
mA Adjustment	0.5 - 4.5 mA
Max X-Ray Power	750 W
Beam Angle	38° x 360°
Leakage Radiation	Max. 5.0 mSv/h
Environment	IP65
Temperature Range	-20°C to +50°C
Cont. Exposure 35°C, 300kV/ 2.5mA	Min. 1 hour

SALES AND MANUFACTURING

+44 (0)1502 500969 - sales@jme.co.uk



ALL GOODS AND SERVICES ARE SOLD SUBJECT TO THE TERMS AND CONDITIONS OF JME. A COPY OF THESE TERMS AND CONDITIONS IS AVAILABLE UPON REQUEST.

ALL BRAND NAMES AND PRODUCT NAMES WHERE USED ARE ACKNOWLEDGED TO BE TRADEMARKS OF THEIR RESPECTIVE HOLDERS.